

SOLVY FABRIC

Main Applications:

- ◆ Any project where you don't want stabilizer residues.
- ◆ Suitable for all fabric types that can be washed.

Processing Recommendations:

- ◆ **Hoooping:**
Back your fabric with SOLVY FABRIC and hoop it.
- ◆ **After Embroidering:** Remove the backing and tear away all excess SOLVY FABRIC.
- ◆ **Washing:** The backing residues will completely wash away during the first wash.

Dissolving Speed:

SOLVY FABRIC dissolves in cold water. The dissolving process clearly speeds up with increased water temperatures.

Dissolving Times:

- 20°C —————> approx. 3 minutes
- 25°C —————> approx. 2 minutes
- 30°C —————> approx. 1 minute
- 40°C —————> approx. 15 seconds

Technical Information:

- ◆ **Special water-soluble backing**
- ◆ **Material:** 100% polyvinylalcohol (PVA)
- ◆ **Storage:** Keep SOLVY FABRIC in a dry place and away from direct sunlight.
- ◆ It leaves no health-hazardous substances in the water!
- ◆ **Make up:**
 - Roll: 200 m x 155 cm width
 - Roll: 25 m x 50 cm width
 - Weight: 40 g/m²
- ◆ **Narrow rolls are available precut**
- ◆ **Minimum order:**
Single rolls



Professional materials for high-quality embroidery results – tried and tested in the clothing, promotion and home textile industries. For more information visit our website www.gunold.de!

Distributed by:



ROTHENBORG ApS

INDUSTRIASYMASKINER
GUDUMKÆRVEJ 6 • DK-7400 HERNING
www.rothenborg.dk • Tlf. +45 97 15 63 33

GUNOLD®



Carbon neutral printing on PEFC and FSC certified paper.