SOLVY FILM 80

Main Applications:

- For soft patches and emblems
- fully embroidered motifs

- lasered applications
- For cutwork embroideries like English or Richelieu embroidery

Processing Recommendations:

(ye)


Patches and Emblems:

- Firmly hoop SOLVY FILM 80 without additional stabilizer.
- Tear out the finished embroidery from the foil.
- dampen the embroidery edges with a damp cloth and you'll have neatly finished edges.
- ◆ There's no need to cut out the patch.

Cutwork Embroideries:


- Firmly hoop SOLVY FILM 80 without additional stabilizer.
- Embroider the design. Important: make sure all design segments are interlinked!
- Dissolve SOLVY FILM 80 in the washing machine.





For fully embroidered patches and openwork patterns, the pattern must be digitized so that all parts of the pattern are connected. Otherwise, the pattern would fall apart after washing out SOLVY FILM 80.

Technical Information:





Material:

75% polyvinyl alcohol / 25% additives

Strength: ca. 100 g/m²

Remove:

- The film dissolves faster in lukewarm water than in cold water.
- Rinse individual pieces by hand while gently
- larger quantities in the washing machine at approx. 30°C.

Storage:

Protect against moisture and drying out. Store in closed plastic bag.

Make-up:

Rolls 100 cm x 100 m 50 cm x 25 m

Minimum Order:

1 roll

Professional materials for high-quality embroidery results – tried and tested in the clothing, promotion and home textile industries. For more information visit our website www.qunold.de!



ROTHENBORG ApS

INDUSTRISYMASKINER GUDUMKÆRVEJ 6 * DK-7400 HERNING www.rothenborg.dk * Tif. +45 97 15 63 33

